

# BETA MAJOR

## A. Adkins and Sons Limited

High Cross, Lancaster Road, Hinckley, Leicestershire LE10 0AW United Kingdom

Tel: +44 (0) 1455 89 12 91 • Fax: +44 (0) 1455 63 35 03

Email: [service@aadkins.com](mailto:service@aadkins.com), [sales@aadkins.com](mailto:sales@aadkins.com) • Web: [www.aadkins.com](http://www.aadkins.com)

Having all the technological advances of our manual press, these have the additional feature of fingertip controlled air operation.

Benefits include user comfort and ease of operation, while maintaining consistent pressure control, making it ideal for high volume production.

A high-efficiency, silent air compressor can be supplied, on request.

The Beta Major is a pneumatically operated heat press for transfer printing and material fusing. It is ideal for high volume production with low operator fatigue.

• Supplied table: 38 cm x 50 cm (15 in x 20 in) - Part No. AMC113

Optional table: 15.3 cm x 15.3 cm (6 in x 6 in) - Part No. AMC584

Optional table: 20.5 cm x 20.5 cm (8 in x 8 in) - Part No. AMC583

Optional table: 25.4 cm x 25.4 cm (10 in x 10 in) - Part No. AMC582

Optional table: 30.5 cm x 30.5 cm (12 in x 12 in) - Part No. AMC581

Optional table: 30.5 cm x 15.3 cm (12 in x 6 in) - Part No. AMC585

Optional table: 38cm x 38 cm (15 in x 15 in) - Part No. AMC123

Optional Umbrella table - Part No. AMC586

- Swing head operation for clear view of working area.
- Fully adjustable and accurate air pressure gauge control.
- Locking air pressure control.
- Emergency stop button.
- Thermal cut out on the heating element shuts off power to the elements if the temperature exceeds 235°C +/- 15°C (455°F +/- 27°F).
- Cast aluminium construction for strength and durability.
- Self adhesive silicone base pad.
- Manufactured and tested to comply with EC safety regulations.
- CE labelled.
- Lifetime heat element guarantee.
- 12 month limited warranty on machine.
- Full service/ spares support.
- Manual supplied illustrates electrical and pneumatic wiring diagrams, exploded diagram and parts list. Full safety instructions.



### Specifications

### European Machine

Power consumption	2500 Watts
Power supply	230-240 Volts AC
Compressed air supply	7 bar max
Compressed air consumption	60 litres/min
Working temperature	70-230°C
Display timer range	0 - 9.59 min
Machine height	52 cm
Machine width	59 cm
Machine width, loading	79 cm
Machine depth	57 cm
Machine depth, loading	104 cm
Work area required	77 kg
Weight export packed	80 x 105 x 52 cm
Size export packed	79(L) x 74(W) x 73 cm(H)
Net weight	69 kg
Press pad dimensions	See above
Fuse	12.5A
A-weighted noise level	<70 dB(A)